



- [Overview](#)
- [Program Overview](#)
- [Go Green](#)
- [Financing](#)
- [Terms & Conditions](#)
- [Recommended Equipment](#)
- [Facility Planning](#)
- [Sales Rep Locator](#)
- [Contact Us](#)

Pricing | Search

[Equipment Catalog](#)

[Login Equipment](#) | [Apply for Access](#) | [Need Assistance](#)

[View Cart](#) Your cart is empty

PRODUCT CATEGORIES

- Welding**
- Spot Welders
- Welder Accessories

**Power Plasma 3035.**  
505-279



- [Add to Order](#)
- [Request a Call](#)
- [Email Link](#)

Dual voltage (110V/220V) Inverter plasma cutter. Infinite output adjustment from 5 to 30 amps with high-frequency arc start. 3/8" maximum cutting capacity on steel. Ideal for cutting Aluminum and Ultra-High-Strength Steels.

**Features**

- Equipped with Power Factor Correction technology (PFC).Complies with IEC/EN 61000-3-12.
- Dual Voltage (110V/220V) auto switch.
- Infinitely adjustable output from 5 to 30 amps.
- Patented plasma torch design for low air consumption.
- Light weight and portable.
- Plug in anywhere.
- Easy to operate.

**Technical**

Weight approx. (lbs)	29
Speed (rpm)	n/a
Power supply (V/Hz/A)	110/220 1PH/50-60/30A
Power consumption (kW)	3.5
Dimensions (L x W x H) (inch)	20 x 7 x 16
Welding cable length (inch)	156

**Other Cebotech, Inc. products:**

- [Power Plasma 3035.](#)
- [Cebora Power Plasma 2025](#)
- [Cebora Power Spot 5600](#)
- [TECNA 3650 EVO](#)
- [CEBORA Synergic Double Pulse MIG 2060/MD](#)